



Drill Driver LXT®

■ DDF453RFE

18V • 42 Nm • 0 – 1 300 min?¹

Tool for drilling and screwdriving for demanding home use

A general-use tool with two speed ranges for screwdriving and drilling. Max. torque of 42 / 27 Nm. Suitable for light professional use or demanding amateur use. Includes 2 x 3,0 Ah batteries and a charger.



■ TECHNICAL SPECIFICATIONS

SOUND PRESSURE LEVEL (LPA)	72 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
■ VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
PRODUCT DIMENSIONS (L X W X H):	214 x 79 x 227 mm
NO LOAD SPEED	0 - 400 / 1300 min? ¹
MAX. DRILLING DIAMETER IN WOOD	36 mm
MAX. DRILLING DIAMETER IN STEEL	13 mm
DRILL CHUCK CAPACITY	1,5 - 13 mm
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	1,7 - 2,0 kg
NOMINAL BATTERY VOLTAGE	18 V
MAX. FASTENING TORQUE HARD/SOFT	42 / 27 Nm
VOLTAGE LXT	Yes
VIBRATION LEVEL (3 AXES), DRILLING	? 2,5 m/s ²
CLUTCH TORQUE SETTING	16
BATTERY CHEMISTRY (NI-CD / NI-MH / LI-ION)	Li-ion
DRIVING SHANK	1/2"-20UNF "

■ USER BENEFITS

- The rubber coating on the handle ensures a firm working grip

Link to Product page - <https://clone.makitauae.com/product/ddf453rfe-drill-driver-lxt/>