



## Hammer Drill Driver LXT®

### DHP453RFE

18V • 42 Nm • 0 – 1 300 min?<sup>1</sup>

**Combi drill with hammer action for demanding amateur builders**

For screwdriving and drilling with or without hammer action, two power settings. Max. torque of 42 / 27 Nm. Suitable for light professional use or demanding amateur use. Includes 2 x 3,0 Ah batteries and a charger in a case.



### TECHNICAL

### SPECIFICATIONS

IMPACT	0 - 6000 / 19 500 min? <sup>1</sup>
SOUND POWER LEVEL (LWA)	94 dB(A)
SOUND PRESSURE LEVEL (LPA)	83 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s <sup>2</sup>
PRODUCT DIMENSIONS (L X W X H):	239 x 79 x 227 mm
EAN	88381661249
NO LOAD SPEED	0 - 400 / 1300 min? <sup>1</sup>
MAX. DRILLING DIAMETER IN WOOD	36 mm
MAX. DRILLING DIAMETER IN CONCRETE	13 mm
MAX. DRILLING DIAMETER IN STEEL	13 mm
DRILL CHUCK CAPACITY	1,5 - 13 mm
VIBRATION LEVEL (3 AXES), IMPACT DRILLING	10,0 m/s <sup>2</sup>
BRUSHLESS MOTOR	Yes
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	1,7 - 2,0 kg
NOMINAL BATTERY VOLTAGE	18 V
MAX. FASTENING TORQUE HARD/SOFT	42 / 27 Nm
VOLTAGE LXT	Yes
VIBRATION LEVEL (3 AXES), DRILLING	? 2,5 m/s <sup>2</sup>
CLUTCH TORQUE SETTING	16
BATTERY CHEMISTRY (NI-CD / NI-MH / LI-ION)	Li-ion
DRIVING SHANK	1/2"-20UNF "
MAX. DRILLING DIAMETER IN MASONRY	13 mm
CAPACITY STANDARD SCREW	187 kpl

### USER BENEFITS

- The rubber coating on the handle ensures a firm working grip

Link to Product page - <https://clone.makitauae.com/product/dhp453rfe-hammer-drill-driver-lxt/>