



Reciprocating Saw LXT®

DJR181RTE

18V • 0 – 2 800 min⁻¹ • 28 mm

High speed for non-sparking metal cutting.

Reciprocating Saw with 18V voltage. High speed for non-sparking metal cutting. Tool change and blade adjustment without tool. Two 5.0Ah batteries and 36 min charger. Includes 2 x 5,0 Ah batteries and a charger in a case.



TECHNICAL

SPECIFICATIONS

IMPACT	0 - 2900 min ⁻¹
SOUND POWER LEVEL (LWA)	95 dB(A)
SOUND PRESSURE LEVEL (LPA)	84 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	18,5 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	2,0 m/s ²
PRODUCT DIMENSIONS (L X W X H):	499 x 91 x 234 mm
BATTERY PROTECTION	Yes
TOOL WEIGHT WITH BATTERY (EPTA)	3,5 - 3,7 kg
NOMINAL BATTERY VOLTAGE	18 V
LENGTH OF STROKE	28 mm
MAX. CUTTING CAPACITY IN WOOD (90°)	255 mm
MAX. CUTTING CAPACITY IN STEEL PIPE	130 mm
VOLTAGE LXT	Yes

USER BENEFITS

- Battery protection system automatically shuts off power when the battery level is low
- Body model - delivered without battery and charger.
- LED light illuminates the work site

Link to Product page - <https://clone.makitauae.com/product/djr181rte-reciprocating-saw-lxt/>