



Circular Saw

■ HS0600

2 000 W • 4 300 min⁻¹ • 260/270 mm

Efficient, very high-capacity circular saw

An efficient and robust high-capacity circular saw with a 2 000 W motor and speed of 4 300 min⁻¹ designed for professional use. Compatible with a blade with 270 mm diameter that achieves a high max. cutting depth of 101 mm.



TECHNICAL

SPECIFICATIONS

| | |
|---|---------------------------|
| MAXIMUM OUTPUT POWER | 2000 W |
| POWER SUPPLY CORD | 2,5 m |
| ■ SOUND POWER LEVEL (LWA) | 105 dB(A) |
| SOUND PRESSURE LEVEL (LPA) | 94 dB(A) |
| NOISE UNCERTAINTY (K FACTOR) | 3 dB(A) |
| VIBRATION LEVEL (3 AXES) | ? 2,5 m/s ² |
| VIBRATION UNCERTAINTY (K FACTOR) | 1,5 m/s ² |
| WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003) | 6,9 kg |
| PRODUCT DIMENSIONS (L X W X H): | 418 x 273 x 324 mm |
| EAN | 88381836029 |
| NO LOAD SPEED | 4300 min ⁻¹ |
| BLADE DIAMETER | 270 mm |
| BORE SIZE (ARBOR DIAMETER) | 15,88 / 20 / 25,4 / 30 mm |
| MAX. CUTTING DEPTH AT 50° | 63 mm |
| MAX. CUTTING DEPTH AT 90° | 101 mm |
| MAX. CUTTING DEPTH AT 45° | 71 mm |
| MAX. BEVEL RANGE (LEFT) | 0 / 45 ° |

USER BENEFITS

Link to Product page - <https://clone.makitauae.com/product/hs0600-circular-saw/>