



Reciprocating Saw

JR3060T

1 250 W • 0 – 2 800 min⁻¹ • 32 mm

Rugged reciprocating saw with three-stage pendulum action

A basic reciprocating saw for spark-free cutting of metal and demolition work. An efficient 1 250 W motor, stroke length of 32 mm and stroke rate of 0 – 2 800 min⁻¹ with continuous control from the switch. Three-stage pendulum action and quick-release blade attachment.



TECHNICAL

SPECIFICATIONS

MAXIMUM OUTPUT POWER	1250 W
IMPACT	0 - 2800 min ⁻¹
POWER SUPPLY CORD	2,5 m
SOUND POWER LEVEL (LWA)	98 dB(A)
SOUND PRESSURE LEVEL (LPA)	87 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION UNCERTAINTY (K FACTOR)	2,0 m/s ²
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	4,4 kg
PRODUCT DIMENSIONS (L X W X H):	485 x 99 x 181 mm
EAN	88381061315
LENGTH OF STROKE	32 mm
MAX. CUTTING CAPACITY IN WOOD (90°)	255 mm
ORBITAL ACTION	Yes
JIG SAW BLADES	Yes

USER BENEFITS

Link to Product page - <https://clone.makitauae.com/product/jr3060t-reciprocating-saw/>